

ILS Y or LOC Y RWY 20R  
KENAI MUNI (ENA) (PAEN)

MALSR

**MISSED APPROACH:** Climb to 1800 then climbing right turn to 4000 on heading 046° and on EDF TACAN R-212 to TBONE INT/EDF 49.2 DME and hold

† Missed approach requires minimum climb of 800 feet per NM to 4000; if unable to meet climb gradient, see ILS Z or LOC Z RWY 20R.

[illegible]

1800 ↑	4000 hdg R-212 046°	EDF R-212	TBONE INT	Use I-ENA DME when on the localizer course.				
*LOC only		TBONE INT I-ENA 11.8		One Minute Holding Pattern				
FREDE I-ENA 5.4		1400		196°		016° → 4500 ← 196° 2000		GS 3.00° TCH 51
I-ENA 1.4		*I-ENA 2.6		1400				
1.2 NM		2.8 NM		6.4 NM				
CATEGORY	A	B	C	D	E			
S-ILS 20R #†	298/24 200 (200-½)							
S-LOC 20R †	520/24 422 (500-½)		520/40 422 (500-¾)					
CIRCLING	560-1	580-1	580-1½	680-2	760-2¼			
	460 (500-1)	480 (500-1)	480 (500-1½)	580 (600-2)	660 (700-2¼)			