

WAAS CH 61220 W05A	APP CRS 047°	Rwy Idg 10004 TDZE 952 Apt Elev 952
--	------------------------	--

RNAV (GPS) RWY 5L

BATTLE CREEK EXECUTIVE AT KELLOGG FIELD (BTL)

RNP APCH

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 37°C.
▲ Rwy 5L helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Grand Rapids altimeter setting: increase all DAs 106 feet and all visibilities ¾ SM; increase all MDAs 120 feet and increase LNAV Cats C and D visibility ¾ SM and Circling Cat C visibility ½ SM and Cat D visibility ¼ SM. VDP and Baro-VNAV NA when using Grand Rapids altimeter setting. Circling Rwy 31 NA at night. Circling NA to Rwy 5R and 23L.

MISSED APPROACH:
Climb to 2500 direct
WIPIL and hold.

ATIS 128.325	GREAT LAKES APP CON ★ 119.2 239.25	BATTLE CREEK TOWER ★ 126.825	GND CON 121.7	UNICOM 122.95	CTAF 126.825 0
-----------------	---------------------------------------	---------------------------------	------------------	------------------	-------------------

