WAAS	APP CRS	Rwy ldg	4400
CH 61116	087°	TDZE	894
W08A		Apt Elev	894

RNAV (GPS) RWY 8

LAKEFIELD (CQA)

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. Baro-VNAV NA. Use Wapakoneta altimeter setting. When not received use James M. Cox Dayton Intl altimeter setting and increase all DA 73 feet and all MDA 80 feet; increase LPV Cats A/B/C visibility ¼ mile, LNAV/VNAV Cats A/B/C visibility ½ mile and LNAV and Circling Cat C visibility ¼ mile.

MISSED APPROACH: Climb to 3000 direct EVOZU and via track 127° to ICREB and hold.

AXV AWOS-3	COLUMBUS APP CON	UNICOM	
128.325	118.425 352.05	122.8 (CTAF)	123.3 L





CATEGORY	A	B	C	D
LPV DA	1221-1¼ 327 (400-1¼)			NA
LNAV/VNAV DA	1278-1¼ 384 (400-1¼)			NA
LNAV MDA	1440-1 546 (600-1)		1440-1½ 546 (600-1½)	NA
CIRCLING	1440-1 546 (600-1)		1440-1½ 546 (600-1½)	NA



REIL Rwys 8 and 26 L
MIRL Rwy 8-26 L

EC-2, 03 DEC 2020 to 31 DEC 2020
EC-2, 03 DEC 2020 to 31 DEC 2020