

WAAS CH <b>61213</b> <b>W31A</b>	APP CRS <b>313°</b>	Rwy Idg TDZE <b>1020</b> Apt Elev <b>1031</b>
----------------------------------------	------------------------	-----------------------------------------------------

RNAV (GPS) RWY 31

ST CLOUD RGNL (STC)

⚠

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Little Falls altimeter setting and increase all DA 76 feet, and all MDA 80 feet; increase LNAV/VNAV all Cats visibility ¼ SM and LNAV Cat C/D visibility ¼ SM. For inop ALS when using Little Falls altimeter setting, increase LPV all Cats visibility to ¾ SM and LNAV Cat C/D visibility to 1 ¾ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 46°C (114°F). Baro-VNAV and VDP NA when using Little Falls altimeter setting.

MALSR

MISSED APPROACH:

Climb to 3000 direct WELOK and hold.

ATIS <b>119.375</b>	MINNEAPOLIS CENTER <b>121.05 397.9</b>	ST. CLOUD TOWER ★ <b>118.25 (CTAF) 0</b>	GND CON <b>123.75</b>	UNICOM <b>123.5</b>
------------------------	-------------------------------------------	---------------------------------------------	--------------------------	------------------------

ELEV 1031	D	TDZE 1020
-----------	---	-----------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).				
4 NM Holding Pattern				
*LNAV only				
*1.2 NM to RW31				
1.2 3.8 NM 6.1 NM				
CATEGORY	A	B	C	D
LPV DA	1220-1/2		200 (200-1/2)	
LNAV/VNAV DA	1379-3/4		359 (400-3/4)	
LNAV MDA	1460-1/2 440 (500-1/2)		1460-3/4 440 (500-3/4)	
CIRCLING	1500-1 469 (500-1)		1500-1 1/2 469 (500-1 1/2)	
			1620-2 589 (600-2)	

ST. CLOUD, MINNESOTA

Amdt 1A 29MAR18

45°33'N-94°04'W

ST CLOUD RGNL (STC)

RNAV (GPS) RWY 31