

WAAS
CH **56635**
W36A

APP CRS
002°

Rwy Idg
TDZE **936**
Apt Elev **936**

RNAV (GPS) RWY 36

WARSAW MUNI (R.A.W)



⚠

NA

Baro-VNAV and VDP NA when using Clinton altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA. When local altimeter not received, use Clinton altimeter setting and increase all DA 53 feet and all MDA 60 feet. Increase LNAV/VNAV all Cats visibility to 1½ mile, LNAV Cats C/D visibility to 1¾ mile and Circling Cat C visibility to 2 and Cat D visibility to 2½ mile.

MISSED APPROACH:
Climb to 2600 direct
WOCAZ and hold.

AWOS-3 118.325	WHITEMAN APP CON ★ 127.45 284.0	CTAF 122.9 0
--------------------------	---	------------------------



CATEGORY	A	B	C	D
LPV DA	1136-1 200 (200-1)			
LNAV/VNAV DA	1215-1 279 (300-1)			
LNAV MDA	1340-1 404 (500-1)	1340-1 404 (500-1½)	1580-1 644 (700-1¾)	1580-2 644 (700-2)
CIRCLING	1340-1 404 (500-1)	1400-1 464 (500-1)	1580-1 644 (700-1¾)	1580-2 644 (700-2)

