

WAAS CH <b>81924</b> <b>W19A</b>	APP CRS <b>193°</b>	Rwy Idg <b>4727</b> TDZE <b>81</b> Apt Elev <b>81</b>
--	------------------------	---

RNAV (GPS) RWY 19  
REPUBLIC (FRG)

RADAR required for procedure entry at ZOSAB.

**T** Baro-VNAV NA when using Isip altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Rwy 19 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Isip altimeter setting and increase all DA 37 feet and all MDA 40 feet; increase LNAV/VNAV all Cats visibility  $\frac{1}{8}$  SM and Circling Cats C/D visibility  $\frac{1}{4}$  SM.

**MISSED APPROACH:**  
Climb to 2000 then  
climbing left turn to  
3000 direct  
DPK VOR/DME  
and hold.

ATIS 126.65	NEW YORK APP CON 128.125 269.0	REPUBLIC TOWER ★ 118.8 (CTAF) 0 279.65	GND CON 121.6 269.6	CLNC DEL 128.25	UNICOM 122.95
----------------	-----------------------------------	---	------------------------	--------------------	------------------