



▼

▲

When local altimeter setting not received, use Pittsburgh Intl altimeter setting and increase MDAs 60 feet and visibility Circling Cats A and D ¼ SM and ZUDLO fix minimums S-28 Cats C/D ¼ SM and Circling Cat C ½ SM. Straight-in Rwy 28 NA at night, Circling Rwy 28 NA at night. Rwy 28 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 3000 then right turn direct EWC VOR/DME and hold.

ATIS 118.35	PITTSBURGH APP CON 124.75 338.2	BEAVER COUNTY TOWER ★ 120.3 (CTAF) 0	GND CON 121.8	CLNC DEL 124.85 (when twr closed)
----------------	------------------------------------	---	------------------	---



CATEGORY	A	B	C	D
S-28	2060-1 807 (900-1)	2060-1 ¼ 807 (900-1 ¼)	2060-2 ½	807 (900-2 ½)
CIRCLING	2060-2	807 (900-2)	2060-2 ½	807 (900-2 ½)
ZUDLO FIX MINIMUMS (DME REQUIRED)				
S-28	1740-1	487 (500-1)	1740-1 ½	487 (500-1 ½)
CIRCLING	1740-1	487 (500-1)	1740-1 ½	487 (500-1 ½)