

WAAS
CH **61214**
W11A

APP CRS
110°

Rwy Idg
TDZE **1729**
Apt Elev **1729**

RNAV (GPS) RWY 11

SCHUYLKILL COUNTY/JOE ZERBEY (ZER)

Baro-VNAV NA when using Selinsgrove altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 45°C (113°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Selinsgrove altimeter setting and increase all DA 261 feet and all MDA 280 feet. Increase LPV and LNAV/VNAV all Cats visibility 1 mile, increase LNAV Cat B ¼ mile and Cat C and Cat D 1 mile, and increase circling Cat B ¼ mile and Cat C and Cat D ¾ mile. VDP NA when using Selinsgrove altimeter setting. Circling NA to Rwy 4 and 22.

MISSED APPROACH:
Climb to 4000 direct ETSIW and hold.

AWOS-3 127.575	HARRISBURG APP CON 118.25 269.45	UNICOM 123.075 (CTAF) 0
--------------------------	--	-----------------------------------

The chart displays the RNAV (GPS) RWY 11 approach. Key features include:

- Holding Patterns:** 4000 ft holding at IRCIT (30 NM to IRCIT NoPT), 4000 ft holding at ODDUB (30 NM to ODDUB), and 4000 ft holding at LIXCA (30 NM to LIXCA).
- Altitudes:** 4000 ft, 3400 ft, 3300 ft, 1839± ft, and 1859 ft.
- Navigation Aids:** EHPUZ (FAF), ETSIW (MISSED APCH FIX), and various waypoints like ODDUB, LIXCA, and IRCIT.
- Angles:** 110°, 290°, 020°, 200°, and 2317°.
- Distances:** 4 NM, 6.1 NM, 3.7 NM, 1.4 NM, and 1.8 NM.

4 NM Holding Pattern		4000 ETSIW		
4000		*LNAV only.		
GP 3.00° TCH 40		110° to RW11		
3400		2523 X 40		
6.1 NM		4599 X 75		
3.7 NM		0.5% UP		
1.4 NM		29°		
CATEGORY	A	B	C	D
LPV DA	1929-¾ 200 (200-¾)			
LNAV/ DA VNAV	2109-1¼ 380 (400-1¼)			
LNAV MDA	2200-1 471 (500-1)	2200-1¼ 471 (500-1¼)	2200-1½ 471 (500-1½)	2200-1½ 471 (500-1½)
CIRCLING	2200-1 471 (500-1)	2200-1½ 471 (500-1½)	2280-2 551 (600-2)	2280-2 551 (600-2)
REIL Rwy 11 and 29 0				
MIRL Rwy 11-29 0				

POTTSVILLE, PENNSYLVANIA

Amcl 2A 29MAR18

SCHUYLKILL COUNTY/JOE ZERBEY (ZER)

40°42'N-76°22'W

RNAV (GPS) RWY 11