RNAV (RNP) Y RWY 27

HELENA RGNL (HLN)

APP CRS	Rwy Idg	TDZE	Apt Elev
267°	9000	3852	3877

GPS required. For uncompensated Baro-VNAV systems, procedure NA below -22°C (-7°F) or above 41°C (105°F). For inoperative MALSR, increase RNP 0.22* visibility to 1, and RNP 0.30# visibility to 1½. Missed approach requires RNP less than 1.0. *Missed approach requires minimum climb of 290 feet per NM to 7700; if unable, see RNAV (RNP) Z RWY 27. #Missed approach requires minimum climb of 270 feet per NM to 7600; if unable, see RNAV (RNP) Z RWY 27.

-17°C

MALSR

MISSED APPROACH: Climb to 13000 on track 267° to ZEKSA, then on track 267° to MUSEW, then on track 267° to JEBSI, then on track 261° to KELTY, then on track 271° track to PIXXI and hold, continue climb-in-hold to 13000.

ATIS	HELENA APP CON ★	HELENA TOWER ★	GND CON	UNICOM
120.4	119.5 229.4	118.3 (CTAF) L 257.8	121.9	122.95



NW-1, 03 DEC 2020 to 31 DEC 2020

NW-1, 03 DEC 2020 to 31 DEC 2020

ELEV 3877 D TDZE 3852



REIL Rwys 9, 17 and 35 L
MIRL Rwys 5-23 and 17-35 L
HIRL Rwy 9-27 L



CATEGORY	A	B	C	D
RNP 0.22 DA*	4140-½ 288 (300-½)			
RNP 0.30 DA#	4294-1 442 (500-1)			

AUTHORIZATION REQUIRED