

LOC I-PDT <b><u>110.3</u></b>	APP CRS <b>254°</b>	Rwy Idg <b>6301</b> TDZE <b>1487</b> Apt Elev <b>1497</b>
----------------------------------	------------------------	---

ILS or LOC RWY 26  
EASTERN OREGON RGNL AT PENDLETON (PDT)

DME required.

**T** Circling to Rwy 1 NA at night. DME from PDT VORTAC. Simultaneous reception of I-PDT and PDT DME required. When local altimeter setting not received, use Walla Walla altimeter setting and increase DA to 1809 and all MDA 140 feet and S-ILS 26 visibility. RVR 2500 and S-LOC 26 Cat C and D to RVR 5500. Increase Circling Cat C visibility 1/4 SM and Circling Cat D visibility 1/2 SM. For inop ALS when using Walla Walla altimeter setting increase S-ILS 26 all Cats visibility to RVR 5000 and S-LOC 26 Cat C and D visibility to 1 1/2 SM. # RVR 1800 authorized with use of FD or AP or HUD to DA, (INA when using Walla Walla altimeter setting).

MALSR




**MISSED APPROACH:**  
Climb to 4000 direct  
PDT VORTAC and  
hold, continue  
climb-in-hold to  
4000.

ASOS 118.325	CHINOOK APP CON ★ 133.15 379.15	PENDLETON TOWER ★ 119.7 (CTAF) 0 257.8	GND CON 121.9 257.8	UNICOM 122.95
-----------------	------------------------------------	---	------------------------	------------------

[illegible]

ELEV 1497	<b>D</b>	TDZE 1487
-----------	----------	-----------



REIL Rwys 11 and 29 **L**  
MIRL Rwy 11-29 **L**  
HIRL Rwy 8-26 **L**

PENDLETON, OREGON  
Amdt 25C 05DEC19

4000      PDT

↑     

\*LOC only

SAYOS  
PDT [7.1]

\*PDT [5.7]

PDT [4.6]

2320\*

FAVUB  
PDT [13.1]

4300

REYOT  
PDT [15]

4300


GARYC INT  
PDT [20]

5600

254°

4800

GS 3.00°  
TCH 55

	1.1	1.4	6 NM	1.9 NM	5 NM	
CATEGORY	A		B	C	D	
S-ILS 26 #	1687/24			200 (200-½)		
S-LOC 26	1880/24 393 (400-½)			1880/35 393 (400-¾)		
 CIRCLING	1920-1 423 (500-1)	1960-1 463 (500-1)	1980-1½ 483 (500-1½)	2200-2¼ 703 (800-2¼)		

EASTERN OREGON RGNL AT PENDLETON (PDT)  
45°42'N-118°51'W ILS or LOC RWY 26