

LOC I-AWO	APP CRS	Rwy Idg	5332
111.5	342°	TDZE	135
		Apt Elev	137

LOC RWY 34

ARLINGTON MUNI (AWO)

ADF required. When local altimeter setting not received use Whidbey Island NAS (Ault Field) altimeter setting and increase all MDA 80 feet and increase S-34 and Circling Cats C and D visibility ¼ mile. For inoperative MALS, increase S-34 Cats C and D visibility to 1¾. For inoperative MALS when using Whidbey Island NAS (Ault Field) altimeter setting, increase S-34 Cat D visibility to 1½.

MALS

MISSED APPROACH: Climb to 1000 then climbing left turn to 2000 direct WATON LOM and hold.

AWOS-3PT	SEATTLE APP CON	CLNC DEL	CTAF
135.625	128.5 306.9	121.725	122.725 0

ADF REQUIRED

Remain within 10 NM

CATEGORY	A	B	C	D
S-34	580-¾	445 (500-¾)	580-1	445 (500-1)
CIRCLING	800-1 663 (700-1)	860-1 723 (800-1)	860-2 723 (800-2)	920-2½ 783 (800-2½)

ELEV 137

TDZE 135

ARLINGTON, WASHINGTON

Amtd 5A 11DEC14

48°10'N-122°10'W

ARLINGTON MUNI (AWO)

LOC RWY 34