

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C (22°F) or above 43°C (109°F). When local altimeter setting not received, procedure NA. Circling NA northwest of Rwy 6-24. DME/DME RNP- 0.3 NA. For inoperative MALSR, increase LPV Cat C visibility to ¾ mile and LNAV Cat C visibility to 2½ miles.

MALSR

AS

⚠

MISSED APPROACH:  
Climb to 2600 direct ZUNAD and hold.

ASOS 135.775	SEATTLE CENTER 128.3 269.0	UNICOM 122.7 (CTAF) 0
-----------------	-------------------------------	--------------------------

ELEV 18

TDZE 16

REIL Rwy 6 0

HIRL Rwy 6-24 0

2600 ZUNAD				
* LNAV Only.				
RW24 2.3 NM to RW24 FODUL 2100 NEYDI 241° 2100 241° 2900 061° 241° 2900 4 NM Holding Pattern LAMMB				
GP 3.50° TCH 55				
CATEGORY	A	B	C	D
LPV DA	226-½	210 (300-½)	286-½ 270 (300-½)	NA
LNAV/VNAV DA	676-1½ 660 (700-1½)			NA
LNAV MDA	800-½ 784 (800-½)	800-¾ 784 (800-¾)	800-1¾ 784 (800-1¾)	NA
CIRCLING	800-1 782 (800-1)	800-1¼ 782 (800-1¼)	800-2½ 782 (800-2½)	NA

HOQUIAM, WASHINGTON

46°58'N-123°56'W

BOWERMAN (HQM)

Amdt 2D 28APR16

RNAV (GPS) RWY 24