

WAAS
CH **49229**
W29A

APP CRS
291°

Rwy Idg
TDZE
Apt Elev

5091
1989
1989

RNAV (GPS) RWY 29

L M CLAYTON (OLF')

⚠

✈

-38°C

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Glasgow altimeter setting and increase all DA 141 feet and all MDA 160 feet and increase LPV all Cats visibility ¾ mile, LNAV/VNAV all Cats visibility ½ mile, LNAV Cats C/D visibility ½ mile, and Circling Cats C/D visibility ½ mile. Baro-VNAV and VDP NA with Glasgow altimeter setting.

MISSED APPROACH:
Climb to 4500 direct
RULIE and hold.

ASOS 118.325	SALT LAKE CENTER 126.85 305.2	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------

ELEV 1989

TDZE 1989

4500

RULIE

*LNAV only.

GETKE 2.9 NM to RW29

1 NM

1.9 NM

3 NM

6 NM

CARAV

4 NM Holding Pattern

291° to RW29

5091 X 100

291°

111°

291°

4800

GP 3.00°

TCH 40

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 29).

2940*

3900

291°

111°

CATEGORY	A	B	C	D
LPV DA	2189-¾ 200 (200-¾)			
LNAV/VNAV DA	2239-⅞ 250 (300-⅞)			
LNAV MDA	2340-1 351 (400-1)			
CIRCLING	2480-1 491 (500-1)	2480-1½ 491 (500-1½)	2540-2 551 (600-2)	

MIRL Rwy 11-29 0

REIL Rwy 11-29 0

WOLF POINT, MONTANA

Amtd 1A 11DEC14

48°06'N-105°35'W

L M CLAYTON (OLF')

RNAV (GPS) RWY 29