

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Tulsa Intl altimeter setting and increase all DA 85 feet and all MDA 100 feet, increase LPV all Cats, LNAV/VNAV all Cats, LNAV and Circling Cat C visibility ¼ mile. Inop table does not apply to LPV all Cats. For inop MALSR, increase LNAV Cat A/B visibility to 1 mile. For inop MALSR when use Tulsa Intl altimeter setting, increase LNAV/VNAV all Cats visibility to 2½ mile, and LNAV Cat A/B visibility to 1 mile. Circling NA east of Rwy 17-35. Baro-VNAV and VDP NA when using Tulsa Intl altimeter setting. Helicopter visibility reduction below ¾ SM NA.

MALSR

AS

MISSED APPROACH:

Climb to 2800 direct ODECU and hold.

AWOS 132.675	KANSAS CITY CENTER 128.8 354.1	CTAF 122.825 0
-----------------	-----------------------------------	-------------------

4 NM Holding Pattern

BUKDY

CUHFX

FAXIT

3100

2400

1580

RWY 17

GP 3.30°

TCH 55

4 NM

2.3 NM

0.6

1.8

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 53).

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	906-¾	212 (200-¾)	944-¾ 250 (300-¾)	NA
LNAV/VNAV DA	1317-1½	623 (700-1½)		NA
LNAV MDA	1240-¾	546 (600-¾)	1240-1⅛ 546 (600-1⅛)	NA
CIRCLING	1380-1	663 (700-1)	1400-2 683 (700-2)	NA

ELEV 717

TDZE 694

176° to RWY 17

AS

0.5% UP

6850 X 100

35

923

MIRL Rwy 17-35 0

REIL Rwy 35 0

BARTLESVILLE, OKLAHOMA

Amtd 1 04FEB16

36°46'N-96°01'W

BARTLESVILLE MUNI (BVO)

RNAV (GPS) RWY 17