


RADAR INSTRUMENT APPROACH MINIMUMS

FORT SMITH, AR

Amdt 8D, 20JUN19 (19171) (FAA)

ELEV 469

FORT SMITH RGNL (FSM)


RADAR-1 120.9 343.75 

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	25		AB	1040/24	594	(600-½)	C	1040/50	594	(600-1)
			D	1040/60	594	(600-1¼)	E	1040-1½	594	(600-1½)
	1		AB	1140-1	692	(700-1)	C	1140-2	692	(700-2)
			D	1140-2¼	692	(700-2¼)	E	1140-2½	692	(700-2½)
	7		AB	1200-½	731	(800-½)	C	1200-1½	731	(800-1½)
			D	1200-1¾	731	(800-1¾)	E	1200-2	731	(800-2)
CIRCLING	ALL RWY		AB	1200-1	731	(800-1)	C	1200-2	731	(800-2)
			D	1200-2¼	731	(800-2¼)	E	1200-2½	731	(800-2½)

When control tower closed ASR not authorized.
Rwy 1 helicopter visibility reduction below ¾ SM not authorized.
Rwy 7 helicopter visibility reduction below ¾ SM not authorized.
Circling CAT E NA when R-2401B active.
Circling NA northwest of Rwy 7 and 19 for CAT E.
For inoperative MALSR, increase S-7 CAT E visibility to 2½ miles, and S-25 CAT E visibility to 2 miles.

HENRY POST AAF (KFSI), OK (Fort Sill) (Amdt 13, 19171 USA)

ELEV 1188

RADAR - (E) 120.55 322.4  NA

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
ASR	36 ²		AB	1600/40	413	(500-¾)
			CDE	1600/50	413	(500-1)
	18		AB	1880-1	692	(700-1)
			CDE	1880-2	692	(700-2)
CIR ¹	18-36		AB	1880-1	692	(700-1)
			C	1880-2	692	(700-2)
			D	1920-2¼	732	(800-2¼)
			E	1940-2¾	752	(800-2¾)

When local altimeter setting not received, use Lawton-Ft Sill Rgnl altimeter setting.
¹Circling NA for CAT E W of Rwy 18-36.
²When ALS inop, increase CAT CDE RVR to 60.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

LAWTON, OK
RADAR-1 - 120.55 322.4

Amdt 4A, 10JAN00 (00010) (FAA)

ELEV 1110

LAWTON-FORT SILL RGNL (LAW)

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	35		ABC	1560-¾	471	(500-¾)	D	1560-1	471	(500-1)
CIRCLING	ALL RWY		AB D	1600-1 1680-2	490 570	(500-1) (600-2)	C	1620-1½	510	(600-1½)

LAWTON, OK
RADAR-2 - 120.55 322.4

Amdt 1B, 08AUG02 (02220) (FAA)

ELEV 1110

LAWTON-FORT SILL RGNL (LAW)

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VS</u>
ASR	17		AB	1620-1	510	(600-1)	CD	1620-1½	510	(600-1½)
CIRCLING	ALL RWY		AB D	1620-1 1680-2	510 570	(600-1) (600-2)	C	1620-1½	510	(600-1½)

OKLAHOMA CITY, OK
WILEY POST (PWA)
RADAR-1 124.6 266.8

Amdt 2A, 07APR11 (11153) (FAA)

ELEV 1299

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	35R		AB D	1840-1 1840-1¾	541 541	(600-1) (600-1¾)	C	1840-1½	541	(600-1½)
CIRCLING	ALL RWY		AB D	1840-1 1880-2	541 581	(600-1) (600-2)	C	1840-1½	541	(600-1½)

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

OKLAHOMA CITY, OK
WILL ROGERS WORLD (OKC)
RADAR-1 124.6 266.8 **T A**

Amdt 21A, 13OCT16 (20030) (FAA) ELEV 1296

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	17L		ABCDE	1680/40	393	(400-¾)
	35R		ABCDE	1680/40	386	(400-¾)
	17R		ABCDE	1680/40	398	(400-¾)
	35L		ABCDE	1680/40	404	(400-¾)
CIRCLING	ALL RWY		A	1740-1¼	444	(500-1¼)
			B	1760-1¼	464	(500-1¼)
			C	1960-1¼	664	(700-1¼)
			D	2000-2¼	704	(800-2¼)
			E	2240-3	944	(1000-3)

For inoperative MALSR, increase S-17L, S-17R, and S-35L CAT E visibility to 1¼.
For inoperative ALSF, increase S-35R CAT E visibility to 1¼.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

TINKER AFB (KTIK), (Oklahoma City) OK (20086 USAF)
RADAR - Ctc OKLAHOMA CITY APP CON (E) 118.95 323.1

ELEV 1291

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	36 ¹		A	1940/24	649	(700-½)
			B	1940/40	649	(700-¾)
			C	1940/60	649	(700-1¼)
			D	1940-1½	649	(700-1½)
			E	1940-1¾	649	(700-1¾)
	18 ²		A	2000/40	733	(800-¾)
			B	2000/50	733	(800-1)
			C	2000-1¾	733	(800-1¾)
			D	2000-2	733	(800-2)
			E	2000-2¼	733	(800-2¼)
CIR ³	36		A	1940-1	649	(700-1)
			B	1940-1¼	649	(700-1¼)
			C	1940-1¾	649	(700-1¾)
			D	1980-2¼	689	(700-2¼)
			E	2040-2¾	749	(800-2¾)
	18		A	2000-1	709	(800-1)
			B	2000-1¼	709	(800-1¼)
			C	2000-2	709	(800-2)
			D	2000-2¼	709	(800-2¼)
			E	2040-2¾	749	(800-2¾)

¹When ALS inop, increase CAT A RVR to 50 and vis to 1 mile, CAT B RVR to 60 and vis to 1¼ miles, CAT C vis to 1¾ miles, CAT D vis to 2 miles, CAT E vis to 2¼ miles.
²When ALS inop, increase CAT A RVR to 50 and vis to 1 mile, CAT B RVR to 60 and vis to 1¼ miles, CAT C vis to 2 miles, CAT D vis to 2¼ miles, CAT E vis to 2½ miles.
³CAT E circling not authorized in sector S of Rwy 13-31 and W of Rwy 18-36.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

TULSA, OK

Amdt 18, 13JAN11 (15008) (FAA)

ELEV 677

TULSA INTL (TUL)

RADAR-1 124.0 338.3 

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	26		AB	1060-1	409	(400-1)	CD	1060-1¼	409	(400-1¼)
			E	1060-1½	409	(400-1½)				
	18L		AB	1080/24	439	(500-½)	C	1080/40	439	(500-¾)
			DE	1080/50	439	(500-1)				
	36R		AB	1140/24	490	(500-½)	C	1140/40	490	(500-¾)
			D	1140/50	490	(500-1)	E	1140/60	490	(500-1¼)
	18R		AB	1080-1	413	(500-1)	CD	1080-1¼	413	(500-1¼)
			E	NA						
	8		AB	1120-1	449	(500-1)	C	1120-1¼	449	(500-1¼)
			DE	1120-1½	449	(500-1½)				
	36L		AB	1180-1	503	(600-1)	CD	1180-1½	503	(600-1½)
			E	NA						
CIRCLING	ALL RWY		AB	1180-1	503	(600-1)	C	1180-1½	503	(600-1½)
			D	1300-2	623	(700-2)	E	1300-2¼	623	(700-2¼)

Circling NA for CAT E South of runway 8-26.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS