

| | | | |
|--|------------------------|--|---|
| WAAS CH 40025 W35D | APP CRS 356° | Rwy Idg 13400 TDZE 563 Apt Elev 607 | RNAV (GPS) RWY 35C DALLAS-FORT WORTH INTL (DFW) |
|--|------------------------|--|---|

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C (25°F) or above 54°C (130°F). For inop ALSF, increase LNAV/VNAV all Cats visibility to RVR 6000. Simultaneous approach authorized with Rwy 36 L/R and Rwy 35R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSF-2

MISSED APPROACH:
Climb to 3000 direct BOSSI and hold.

| | | | | | |
|--|------------------------------------|---|---|---------------------------|-------|
| D-ATIS ARR 123.775 DEP 135.925 | REGIONAL APP CON 127.075 | DFW TOWER 126.55 127.5 EAST 124.15 134.9 WEST | GND CON 121.65 121.8 EAST 121.85 WEST | CLNC DEL 128.25 | CPDLC |
|--|------------------------------------|---|---|---------------------------|-------|

