

WAAS

CH **57999**

W35A

APP CRS

353°

Rwy Idg

6002

TDZE

697

Apt Elev

700

RNAV (GPS) RWY 35L

FORT WORTH SPINKS (FWS)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 39°C (102°F). Circling NA west of Rwy 17R-35L. DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Fort Worth Meacham altimeter setting and increase all DA 37 feet and all MDA 40 feet, increase LNAV/VNAV all Cats visibility ⅓ mile. For inop MALSR increase LNAV/VNAV all Cats visibility to 1⅓ mile and increase LNAV Cats C/D visibility to 1⅓ mile. For inop MALSR when using Fort Worth Meacham altimeter setting, increase LNAV/VNAV all Cats visibility to 1¼ mile and LNAV Cats C/D visibility to 1⅓ mile.

MALSR

⬆

A6

MISSED APPROACH:

Climb to 1400 then climbing left turn to 3100 direct SLUGG and hold.

ATIS 120.025	REGIONAL APP CON 135.975 379.9	SPINKS TOWER ★ 124.625 (CTAF) 0	GND CON 119.475	UNICOM 122.7
------------------------	--	--	---------------------------	------------------------

RADAR REQUIRED

4 NM

041°

221°

SLUGG

FEVER

2600

077°

(10.1)

1772

Δ

Δ 978

1009

Δ

RW35L

Δ 831

Δ 899 ±

Δ 988

OPSIY

2 NM to RW35L

919 ±

Δ

1027

(FAF)

RAZOS

2300

353°

(7)

(IF)

CUNVA

2400

083°

(7.9)

(IAF)

ZABVA

MSA 35L 25 NM

3600

ELEV 700

TDZE 697

1400

3100

SLUGG

↑

↶

Δ

*LNAV only.

OPSIY

2 NM to RW35L

RAZOS

2300

CUNVA

2400

353°

GP 3.00°

TCH 50

1360*

2300

1.3

0.7

2.9 NM

7 NM

CATEGORY	A	B	C	D
LPV DA	897-1½ 200 (200-½)			
LNAV/VNAV DA	1193-1¼ 496 (500-1¼)			
LNAV MDA	1160-½	463 (500-½)	1160-1	463 (500-1)
CIRCLING	1200-1	500 (500-1)	1200-1½ 500 (500-½)	1260-2 560 (600-2)

TWR

6002 X 100

4002 X 40

35R

792

Δ

17R

17L

35L

353° to RW35L

MIRL Rwy 17R-35L

FORT WORTH, TEXAS
Amdt 1A 02APR15
32°34'N-97°18'W

FORT WORTH SPINKS (FWS)
RNAV (GPS) RWY 35L