

APP CRS  
**176°**

Rwy Idg  
**8301**

TDZE  
**35**

Apt Elev  
**36**

RNAV (RNP) Z RWY 17R

VALLEY INTL (HRL)

▼

For uncompensated Baro-VNAV systems, procedure NA below 2°C (36°F) or above 54°C (130°F). For inoperative MALSR, increase RNP 0.3 all Cats visibility to RVR 4500. GPS Required.

MALSR

MISSED APPROACH: Climb to 500 then climbing left turn to 2000 direct RELAX and hold.

ATIS <b>124.85</b>	VALLEY APP CON <b>120.7 279.5</b>	HARLINGEN TOWER★ <b>119.3(CTAF) 0 317.6</b>	GND CON <b>121.7</b>	UNICOM <b>122.95</b>
-----------------------	--------------------------------------	--	-------------------------	-------------------------

RADAR REQUIRED

ELEV 36

D

TDZE 35

500

2000

RELAX

CIXEN 1100

1100

GP 3.00°

TCH 55

CATEGORY	A	B	C	D
RNP 0.30 DA	305/40	270 (300-3/4)		

AUTHORIZATION REQUIRED

HARLINGEN, TEXAS

Orig-A 02APR15

26°14'N-97°39'W

RNAV (RNP) Z RWY 17R

VALLEY INTL (HRL)

SC-3, 03 DEC 2020 to 31 DEC 2020