RNAV (GPS) RWY 17

TRENT LOTT INTL (PQL)

WAAS	APP CRS	Rwy Idg	6500
CH 58204	168°	TDZE	17
W17A		Apt Elev	17

TA For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C (23°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Mobile Rgnl altimeter setting: increase LPV DA to 292 feet and LNAV/VNAV DA to 357 feet. Increase LNAV/VNAV visibility ⅛ mile all Cats; increase all MDA 80 feet and LNAV Cat C/D visibility ¼ mile and Circling Cat C/D visibility ½ mile. Baro-VNAV and VDP NA with Mobile Rgnl altimeter setting. For inop MALSRs when using Mobile Rgnl altimeter setting increase LPV all Cats visibility to ⅞ mile.

MALSR

MISSED APPROACH: Climb to 800 then climbing left turn to 1800 direct BEZJU and hold.

ATIS	MOBILE APP CON ★	TRENT LOTT TOWER ★	GND CON	CLNC DEL	UNICOM
135.175	121.0 307.1	118.575 (CTAF) L	121.725	121.725	122.8





CATEGORY	A	B	C	D
LPV DA	217-½ 200 (200-½)			
LNAV/VNAV DA	282-½ 265 (300-½)			
LNAV MDA	380-½ 363 (400-½)		380-⅝ 363 (400-⅝)	
C CIRCLING	480-1 463 (500-1)	680-1 663 (700-1)	680-1¾ 663 (700-1¾)	680-2 663 (700-2)



SC-4, 03 DEC 2020 to 31 DEC 2020
SC-4, 03 DEC 2020 to 31 DEC 2020