


SE-1, 03 DEC 2020 to 31 DEC 2020

D-ATIS 135.1
CINC DEL 126.05
CPDLC
GND CON
121.9 348.6
NASHVILLE TOWER
118.6 257.8
NASHVILLE DEP CON
118.4 360.7



TAKEOFF MINIMUMS:
Rwys 2C, 2L, 2R, 13, 20C, 20L, 20R, 31: Standard
with minimum climb of 500' per NM to 1100.

TOP ALTITUDE:
4000

- NOTE: DME/DME/IRU or GPS required.
RNAV 1.
NOTE: Radar required.
NOTE: For Turbojet aircraft only.
NOTE: Transponder code will be issued via PDC or
Nashville clearance delivery.
NOTE: If unable to accept climb rates, advise ATC
on initial contact.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWYS 2L/C/R: Climb heading 021° or assigned ATC heading, thence....
TAKEOFF RWY 13: Climb heading 136° or assigned ATC heading, thence....
TAKEOFF RWYS 20L/C/R: Climb heading 201° or assigned ATC heading, thence....
TAKEOFF RWY 31: Climb heading 316° or assigned ATC heading, thence....
....expect radar vectors to CHPPY, then on track 115° to EVVAN. Maintain 4000,
expect clearance to filed altitude within five (5) minutes after departure.

NOTE: Chart not to scale.

SE-1, 03 DEC 2020 to 31 DEC 2020