

LOC I-UCY
109.7

APP CRS
006°

Rwy Idg **6503**
TDZE **346**
Apt Elev **346**

ILS or LOC RWY 1
EVERETT-STEWART RGNL (UCY)

ADF required. When local altimeter setting not received, use Dyersburg altimeter setting and increase all DA 72 feet and all MDA 80 feet, increase S-LOC 1 Cat C/D visibility to 1½ mile, Circling Cat C visibility to 1½ mile and Circling Cat D visibility to 2½ mile. Inop table does not apply to S-ILS 1. For inop ODALS, increase S-LOC 1 Cat C/D visibility to 1½ mile. For inop ODALS when using Dyersburg altimeter setting, increase S-ILS 1 all Cats visibility to ¾ mile and S-LOC 1 Cat D visibility to 1½ mile.

ODALS

MISSED APPROACH:
Climb to 1300 then climbing right turn to 2500 direct OBION LOM and hold.

AWOS-3 135.325	MEMPHIS CENTER 133.65 292.15	UNICOM 122.7 (CTAF) 0
--------------------------	--	---------------------------------

ADF and RADAR
REQUIRED

CATEGORY	A	B	C	D
S-ILS 1	546-¾ 200 (200-¾)			
S-LOC 1	820-¾ 474 (500-¾)	820-1¼ 474 (500-1¼)		
CIRCLING	820-1 474 (500-1)	820-1½ 474 (500-1½)	1020-2¼ 674 (700-2¼)	

ELEV 346 TDZE 346

MIRL Rwy 1-19
REIL Rwys 1 and 19

Knots	60	90	120	150	180
Min:Sec	4:24	2:56	2:12	1:46	1:28

UNION CITY, TENNESSEE
Amdt 3 21JUL16

36°23'N-88°59'W

EVERETT-STEWART RGNL (UCY)
ILS or LOC RWY 1