

LOC I-RUQ <b>109.95</b>	APP CRS <b>202°</b>	Rwy Idg TDZE Apt Elev <b>5501</b> <b>772</b> <b>772</b>	ILS or LOC RWY 20 MID-CAROLINA RGNL (RUQ)
----------------------------	------------------------	--	--

ADF required. When local altimeter setting not received, use Lexington altimeter setting and increase all DA 37 feet and all MDA 40 feet; increase S-LOC Cats C/D visibility 1/8 SM and Circling Cat D visibility 1/4 SM. For inop ALS when using Lexington altimeter setting, increase S-LOC 20 Cats C and D visibility to 1 3/4 mile.

MALSR

MISSED APPROACH: Climb to 1600 then climbing right turn to 2900 direct ROVDY LOM and hold.

AWOS-3 <b>118.175</b>	CHARLOTTE APP CON <b>128.325 307.8</b>	CLNC DEL <b>127.35</b>	UNICOM <b>122.725 (CTAF)</b>
--------------------------	---	---------------------------	---------------------------------

ADF REQUIRED

BARRETT'S MOUNTAIN  
110.8 BZM  
Chan 45

2323

GREENSBORO  
116.2 GSO  
Chan 109

2900  
236°  
(31.3)

17

ALTERNATE MISSED  
APCH FIX

AZELL INT  
GSO

17

116.2 GSO  
R-231  
Chan 109

113.0 LIB  
R-278  
Chan 77

1051°

231°

LOCALIZER 109.95  
I-RUQ

LOM/IAF  
ROVDY  
275 RU

1057

1060

988±

1453

1848

1730

202°

022°

133°

15°

202°

022°

3900  
108°  
(37.5)

22.9

3400  
071°  
(22.5)

22.9

3400

MSA RU 25 NM

3400

ELEV 772 TDZE 772

202° 5 NM from FAF

022°

5501 X 100

MIRL Rwy 2-20

REIL Rwys 2 and 20

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

1600	2900	ROVDY		
ROVDY RU LOM	2422	022°	2500	
Remain within 10 NM		202°	2500	
GS 3.00°			TCH 46	
5 NM				
CATEGORY	A	B	C	D
S-ILS 20		972-1/2	200 (200-1/2)	
S-LOC 20	1360-1/2	588 (600-1/2)	1360-1/4	588 (600-1/4)
CIRCLING	1360-1	588 (600-1)	1440-1 3/4 668 (700-1 3/4)	1440-2 668 (700-2)

SALISBURY, NORTH CAROLINA

Amdt 1C 27FEB20

35°39'N-80°31'W

MID-CAROLINA RGNL (RUQ)  
ILS or LOC RWY 20