

LOC/DME I-SVH

111.75

Chan **54** (Y)

APP CRS

285°

Rwy Idg

5456

TDZE

967

Apt Elev

968

ILS Z or LOC Z RWY 28

STATESVILLE RGNL (SVH)

When local altimeter setting not received, use Lincolnton altimeter setting and increase ILS DA to 1219 and all MDA 60 feet; increase S-LOC 28 Cats C/D visibility 1/8 mile and Circling Cat C visibility 1/4 mile. VDP NA when using Lincolnton altimeter setting. For inop MALSR when using Lincolnton altimeter setting, increase S-ILS 28 all Cats visibility to 3/8 mile and S-LOC 28 Cats C/D visibility to 1 mile. DME required.

MALSR

MISSED APPROACH: Climb to 1700 then climbing left turn to 3400 on heading 105° and CLT VOR/DME R-025 to PEGTE INT/I-SVH 13.2 DME and hold.

AWOS-3 119.225	ATLANTA CENTER 125.15 263.0	UNICOM 123.075 (CTAF) 1
--------------------------	---------------------------------------	-----------------------------------

<div>REIL Rwy 10 1</div> <div>HIRL Rwy 10-28 1</div>	1700	3400	CLT R-025	PEGTE △	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 50).				One Minute Holding Pattern	
	*LOC only.		ICENU I-SVH [3.6]		2600	285°	105°	3400	GS 3.00° TCH 50	
			I-SVH [1.2]	*I-SVH [2]	*I-SVH [3.6]	2600	285°	105°		
					*1760	2600	285°	105°		
							2600	285°		
CATEGORY	A		B		C		D			
S-ILS 28			1167-1/2		200 (200-1/2)					
S-LOC 28			1280-1/2		313 (400-1/2)					
CIRCLING	1420-1 452 (500-1)		1540-1 572 (600-1)		1540-1 1/2 572 (600-1 1/2)		1560-2 592 (600-2)			

STATESVILLE, NORTH CAROLINA

Amdt 1A 12OCT17

35°46'N-80°57'W

STATESVILLE RGNL (SVH)

ILS Z or LOC Z RWY 28