

WAAS CH <b>48819</b> <b>W03A</b>	APP CRS <b>032°</b>	Rwy Idg <b>5500</b> TDZE <b>147</b> Apt Elev <b>164</b>
--	------------------------	---

RNAV (GPS) RWY 3  
JOHNSTON RGNL (JNX)

**▼** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Erwin altimeter setting and increase LPV DA to 447 feet, LNAV/VNAV DA to 1020 feet, and all LNAV/VNAV visibilities ½ mile. Increase all MDA 60 feet; increase visibility Cat B, C, and D ¼ mile. Baro-VNAV and VDP NA with Erwin altimeter setting. Inop table does not apply to LNAV/VNAV when using Erwin altimeter setting. For inop MALSR when using Erwin altimeter setting, increase LPV all Cats visibility to 1 mile and LNAV Cats C/D visibility to 2½ miles.

MALSR



**MISSED APPROACH:**  
Climb to 3400 direct  
JNALL and hold,  
continue climb-in-hold  
to 3400.

AWOS-3 <b>120.225</b>	RALEIGH APP CON <b>125.3 353.675</b>	GCO <b>135.075</b>	UNICOM <b>122.725</b> (CTAF) <b>L</b>
--------------------------	---	-----------------------	--

