

WAAS CH 45503 W09A	APP CRS 094°	Rwy Idg TDZE 66 Apt Elev 83
----------------------------------------	------------------------	-------------------------------------------------

RNAV (GPS) RWY 9

TALLAHASSEE INTL (TLH)

RNP APCH

▼


Rwy 9 helicopter visibility reduction below RVR 4000 NA.

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C.

MISSED APPROACH: Climb to 3000 direct FEKAD and hold.

ATIS 119.45 239.25	TALLAHASSEE APP CON ★ 135.8 317.4	TALLAHASSEE TOWER ★ 118.7 (CTAF) 0 257.8	GND CON 121.9 348.6	CLNC DEL 126.65 275.8	UNICOM 123.075
------------------------------	---------------------------------------------	-----------------------------------------------------------	-------------------------------	---------------------------------	--------------------------



4 NM Holding Pattern

RAGKO

HEGET

XOTNE 2.2 NM to RW09

*1.1 NM to RW09

RW09

*800

6 NM

3.1 NM

1.1 NM

1.1 NM

3000

FEKAD

*LNAV only.

GP 3.00°

TCH 58

CATEGORY	A	B	C	D
LPV DA		401/60	335 (400-1¼)	
LNAV/VNAV DA		447-1¼	381 (400-1¼)	
LNAV MDA	480/55	414 (400-1)	480/60	414 (400-1¼)
CIRCLING	580-1 497 (500-1)	600-1 517 (600-1)	640-1½ 557 (600-1½)	800-2¼ 717 (800-2¼)

