

VORTAC OCF

113.7

Chan 84

APP CRS

354°

Rwy Idg

6347

TDZE

80

Apt Elev

89

VOR RWY 36

OCALA INTL-JIM TAYLOR FIELD (OCF)

When local altimeter setting not received, use Gainesville altimeter setting and increase all MDA 100 feet; increase S-36 Cats C and D, and Circling Cat C visibility ¼ mile. For inoperative MALSR, increase S-36 Cats A and B visibility to 1 mile. For inoperative MALSR when using Gainesville altimeter setting, increase S-36 Cats A and B visibility to 1 mile. VDP NA when using Gainesville altimeter setting.

MALSR

MISSED APPROACH: Climb to 2000 via OCF VORTAC R-355 to LEJCO INT/OCF 10 DME and hold.

ATIS 128.125	JACKSONVILLE APP CON 118.6 251.15	OCALA TOWER ★ 119.25 (CTAF) 0	GND CON 121.4	UNICOM 123.0
-----------------	--------------------------------------	----------------------------------	------------------	-----------------

The main enroute chart displays the following features:

- Arrival Path:** 112.0 CTY Chan 57 → R-112 → LEJCO INT OCF 10 → R-355.
- Altitudes:** 175°, 355°, 260, 1448, 666, 564, 299, 321, 276, 354°, 219°, 350°.
- Obstacles:** A 276, A 299, A 321, A 564, A 666, A 1448.
- Navigation Aids:** IAF Ocala 113.7 OCF Chan 84, LEJCO INT OCF 10.
- Other:** 112.0 CTY Chan 57, R-174.

ELEV 89

D

TDZE 80

3009 X 50

81

7467 X 150

36

354° to OCF VORTAC

TWR 149

36

354°

HIRL Rwy 18-36

0

2000

LEJCO

OCF R-355

OCF VORTAC

174°

1700

354°

OCF 2.7

1.7

Remain within 10 NM

CATEGORY	A	B	C	D
S-36	640-¾ 560 (600-¾)		640-1 560 (600-1)	640-1¼ 560 (600-1¼)
CIRCLING	640-1 551 (600-1)		640-1½ 551 (600-1½)	640-2 551 (600-2)

OCALA, FLORIDA

Amdt 18 15JAN09

29°10'N-82°13'W

OCALA INTL-JIM TAYLOR FIELD (OCF)

VOR RWY 36