

OAKLAND FIVE DEPARTURE

AL-294 (FAA)

METROPOLITAN OAKLAND INTL (OAK)  
OAKLAND, CALIFORNIA

D-ATIS  
133.775  
CLNC DEL  
121.1  
CPDLC  
NORCAL DEP CON  
120.9 323.2

TOP ALTITUDE:  
ASSIGNED BY ATC

MENDOCINO  
112.3 ENI  
Chan 70  
N39°03.19'-W123°16.46'  
L-2, H-3

RED BLUFF  
115.7 RBL  
Chan 104  
N40°05.93'-W122°14.18'  
L-2, H-3

SACRAMENTO  
115.2 SAC  
Chan 99  
N38°26.62'-W121°33.10'  
L-2-3, H-3

SCAGGS ISLAND  
112.1 SGD  
Chan 58  
N38°10.76'-W122°22.39'  
L-2-3

GRTFL  
DEDHD

ORRCA  
MOGEE

TIPRE

SYRAH

LINDEN  
114.8 LIN  
Chan 95  
N38°04.47'-W121°00.23'  
L-2-3, H-3

ALCOA  
N37°50.00'-W125°50.07'  
H-3

OAKLAND  
116.8 OAK  
Chan 115  
N37°43.56'-W122°13.42'  
L-2-3, H-3

BEBOP  
N37°00.00'-W125°00.07'  
H-3

SEGUL  
N36°57.78'-W122°34.33'  
△

WOODSIDE  
113.9 OSI  
Chan 86  
N37°23.55'-W122°16.88'  
L-2-3, H-3

NTELL

CINNY

CYPRS  
N36°25.34'-W122°25.93'  
△

PANOCHÉ  
112.6 PXN  
Chan 73  
N36°42.93'-W120°46.72'  
L-3, H-3

EBAYE  
LOSHN

CISCO

AVENAL  
117.1 AVE  
Chan 118  
N35°38.82'-W119°58.72'  
L-3-7, H-4

FELLOWS  
117.5 FLW  
Chan 122  
N35°05.59'-W119°51.93'  
L-3-7, H-4

NOTE: Chart not to scale.

TAKEOFF MINIMUMS

Rwys 15, 33: NA- ATC.  
Rwy 10L: Standard with minimum climb of 340' per NM to 2300.  
Rwy 10R: Standard with minimum climb of 330' per NM to 2300.  
Rwy 12: Standard with minimum climb of 270' per NM to 1400.  
Rwys 28L/R, 30: Standard with minimum climb of 375' per NM to 2000.

NOTE: RADAR required.  
NOTE: DME required.  
NOTE: Use the SILENT, HUSSH, or SUNNE DEPARTURE during the periods of 2200-0700 local in lieu of the OAKLAND DEPARTURE.

(NARRATIVE ON FOLLOWING PAGE)

OAKLAND FIVE DEPARTURE

SW-2, 03 DEC 2020 to 31 DEC 2020

SW-2, 03 DEC 2020 to 31 DEC 2020