

LOC/DME I-EVV  
**109.9**  
Chan **36**

APP CRS  
**221°**

Rwy Idg  
TDZE **422**  
Apt Elev **422**

ILS or LOC RWY 22

EVANSVILLE RGNL (E V V)

ASR

Circling Rwy 9 NA at night.  
# RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1000 then climbing right turn to 2500 direct PXV VORTAC and hold.

ATIS <b>120.2</b>	EVANSVILLE APP CON ★ <b>124.025 290.9</b>	EVANSVILLE TOWER ★ <b>118.7(CTAF) 257.8</b>	GND CON <b>121.9</b>	CLNC DEL <b>126.6</b>	UNICOM <b>122.95</b>
----------------------	--	--	-------------------------	--------------------------	-------------------------

OWENSBORO  
OWB  
108.6  
Chan 23

ALT MISSED  
APCH FIX

310° R-130°

MSA PXV 25 NM

2500

Procedure NA for arrival on PXV  
VORTAC airway radials 013 CW 081.

POCKET CITY  
113.3 PXV  
Chan 80

2500 to CUYAR  
048° (20.1)

R-237-057°  
237°

(IAF)  
CUYAR INT  
I-EVV **7.9**  
PXV **20.1**

961  
606  
703  
1490  
730  
544  
730  
1449

LOCALIZER 109.9  
I-EVV  
Chan 36

221°

176°  
356°  
041°  
221° (6.2)

(IF)  
JISEV INT  
I-EVV **14.1**

2500 NoPT  
221° (7.4)  
I-EVV **21.5**

R-347  
108.6 OWB  
Chan 23

1000 2500 PXV

\* LOC only  
I-EVV **1.5**

\* I-EVV  
2.7

ZAGAK  
I-EVV **3.5**

CUYAR INT  
I-EVV **7.9**

2500

041°

221°

2500

1080\*

1.2 NM 0.8 NM 4.4 NM

GS 3.00°  
TCH 50

Remain  
within 10 NM

CATEGORY	A	B	C	D
S-ILS 22	# 622/24		200 (200-½)	
S-LOC 22	1080/24	658 (700-½)	1080-1¾	658 (700-1¾)
CIRCLING	1080-1	658 (700-1)	1080-1¾ 658 (700-1¾)	1080-2 658 (700-2)
ZAGAK FIX MINIMUMS (DME REQUIRED)				
S-LOC 22	860/24	438 (500-½)	860/40	438 (500-¾)
CIRCLING	920-1 498 (500-1)	1040-1 618 (700-1)	1040-1¾ 618 (700-1¾)	1040-2 618 (700-2)

ELEV 422

TDZE 422

221° 6.4 NM  
from FAF

434  
439  
8021 X 150  
3497  
X 75  
391  
553  
447

36 HIRL Rwy 4-22 and 18-36  
REIL Rwy 4, 18, and 36  
MIRL Rwy 9-27

FAF to MAP 6.4 NM

Knots 60 90 120 150 180

Min:Sec 6:24 4:16 3:12 2:34 2:08

EVANSVILLE, INDIANA

Amtd 23 02MAR17

38°02'N-87°32'W

EVANSVILLE RGNL (E V V)

ILS or LOC RWY 22