

WAAS CH 65641 W22A	APP CRS 217°	Rwy Idg TDZE Apt Elev	5500 904 904
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 22

BOLTON FIELD (TZR)

⚠

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using John Glenn Columbus Intl altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received use John Glenn Columbus Intl setting and increase LPV DA to 1196 feet and LNAV/VNAV DA to 1382 feet and all MDA 60 feet; increase LPV and LNAV/VNAV all Cats visibility 1⁄8 SM, and LNAV Cat C/D visibility 1⁄4 SM.

MISSED APPROACH:
Climb to 2700 direct
WATIG and hold.

AWOS-3 135.925	COLUMBUS APP CON 134.0 279.6	BOLTON TOWER ★ 128.1 (CTAF) 0	GND CON 121.8
--------------------------	--	---	-------------------------

RADAR REQUIRED

ELEV 904

TDZE 904

217° to RW22

TWR 972

500x100

1027

REIL Rwy 22

MIRL Rwy 4-22

2700

WATIG

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 25).

* LNAV only.

OPOKE

HARIP

RW22

* 1.2 NM to RW22

2300

3000

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	1154-7⁄8 250 (300-7⁄8)			
LNAV/VNAV DA	1339-1½ 435 (500-1½)			
LNAV MDA	1320-1 416 (500-1)	1320-1½ 416 (500-1½)		
CIRCLING	1360-1 456 (500-1)	1380-1 476 (500-1)	1380-1½ 476 (500-1½)	1500-2 596 (600-2)