

WAAS CH <b>53520</b> <b>W21A</b>	APP CRS <b>212°</b>	Rwy ldg TDZE Apt Elev	<b>6600</b> <b>1661</b> <b>1661</b>
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 21

BISMARCK MUNI (BIS)

RNP APCH.

ASR

-35°C

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C.

MISSED APPROACH:

Climb to 4500 direct AXAXE and hold.

ATIS

119.35

BISMARCK APP CON ★

126.3 298.9

BISMARCK TOWER★

118.3(CTAF) 0 257.8

GND CON

121.9

UNICOM

122.95

MISSED APCH FIX  
AXAXE

5 NM

4500

AXAXE

\*LNAV only.

\*1.2 NM to RW21

2500\*

1.2

1.3

3.4 NM

6.1 NM

WULAB 2.5 NM to RW21

EHTIP 3600

HUFMU

4 NM Holding Pattern

032°

212°

6000

4000

GP 3.00°

TCH 48

CATEGORY	A	B	C	D
LPV DA		1861-3/4	200 (200-3/4)	
LNAV/VNAV DA		1970-7/8	309 (400-7/8)	
LNAV MDA	2100-1	439 (500-1)	2100-1 1/4	439 (500-1 1/4)
CIRCLING	2200-1	539 (600-1)	2460-2 1/4 799 (800-2 1/4)	2460-2 1/2 799 (800-2 1/2)

ELEV 1661

D

TDZE 1661

REIL Rwys 3 and 21  
HIRL Rwys 3-21 and 13-31