

WAAS
CH **82106**
W12A

APP CRS
125°

Rwy Idg
TDZE **1183**
Apt Elev **1183**

RNAV (GPS) RWY 12

SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FIELD (MML)

⚠

Baro-VNAV and VDP NA when using Tracy Muni altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 36°C (96°F). When local altimeter setting not received, use Tracy Muni altimeter setting and increase all DA 58 feet and all MDA 60 feet. Increase LNAV/VNAV and LNAV Cats C/D visibility to ¾ mile. DME/DME RNP-0.3 NA. For inoperative MALSR, increase LNAV Cats C/D visibility to 1 mile. For inoperative MALSR when using Tracy Muni altimeter setting, increase LPV all Cats to ½ mile.

MALSR

MISSED APPROACH:
Climb to 3000 direct BOPMY and hold.

AWOS-3PT 120.150	MINNEAPOLIS CENTER 127.1 290.2	GCO 121.725	UNICOM 122.8 (CTAF)
----------------------------	--	-----------------------	-------------------------------

4 NM Holding Pattern

3200 ← 305°
125° →

GP 3.00°
TCH 49

PELBE

HIBUM

DABLE 2 NM to RW12

*1860

*1 NM to RW12

RW12

3000

BOPMY

125° to RW12

*LNAV only

CATEGORY	A	B	C	D
LPV DA		1383- ½	200 (200-½)	
LNAV/VNAV DA		1490- ½	307 (400-½)	
LNAV MDA	1560- ½	377 (400-½)	1560- ⅝	377 (400-⅝)
CIRCLING	1640-1	457 (500-1)	1640-1 ½	1740-2
			457 (500-1 ½)	557 (600-2)

ELEV 1183

TDZE 1183

HIRL Rwy 12-30

REIL Rws 2 and 20

MIRL Rwy 2-20

MARSHALL, MINNESOTA

Amdt 1A 28MAY15

SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FIELD (MML)

44°27'N-95°49'W

RNAV (GPS) RWY 12