

WAAS CH 86315 W33A	APP CRS 331°	Rwy Idg 6600 TDZE 1021 Apt Elev 1021
--	------------------------	---

RNAV (GPS) RWY 33
MANKATO RGNL (MKT)

MANKATO RGNL (MKT)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 46°C (114°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Waseca altimeter setting to increase LPV DA to 1278 feet, LNAV/VNAV DA to 1432 feet and LNAV/VNAV visibility ½ mile all Cats; increase all MDA 60 feet and LNAV Cats C and D visibility ½ mile.

▲ For inoperative MALSR when using Waseca altimeter setting, increase LPV all Cats visibility to ¾ mile and LNAV Cat C and D visibility to 1 ½ mile. Baro-VNAV and VDP NA when using Waseca altimeter setting. For inoperative MALSR, increase LNAV/VNAV all Cats visibility to 1 ½ mile and LNAV Cats C and D visibility to 1 mile.

MALSR



MISSED APPROACH:
Climb to 2700 direct
HIBOG and hold.

AWOS-3PT 118.175	MINNEAPOLIS CENTER 135.0 306.9	UNICOM 122.725 (CTAF) 0
----------------------------	--	-----------------------------------

