

WAAS CH 61213 W31A	APP CRS 313°	Rwy Idg TDZE 1020 Apt Elev 1031
--	------------------------	---

RNAV (GPS) RWY 31

ST CLOUD RGNL (STC)

⚠

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Little Falls altimeter setting and increase all DA 76 feet, and all MDA 80 feet; increase LNAV/VNAV all Cats visibility ¼ SM and LNAV Cat C/D visibility ¼ SM. For inop ALS when using Little Falls altimeter setting, increase LPV all Cats visibility to ¾ SM and LNAV Cat C/D visibility to 1 ¾ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 46°C (114°F). Baro-VNAV and VDP NA when using Little Falls altimeter setting.

MALSR

MISSED APPROACH:

Climb to 3000 direct WELOK and hold.

ATIS 119.375	MINNEAPOLIS CENTER 121.05 397.9	ST. CLOUD TOWER ★ 118.25 (CTAF) 0	GND CON 123.75	UNICOM 123.5
------------------------	---	---	--------------------------	------------------------

ELEV 1031

D

TDZE 1020

3000 WELOK VGS1 and RNAV glidepath not coincident (VGS1 Angle 3.00/TCH 50). 4 NM Holding Pattern				
CATEGORY	A	B	C	D
LPV DA	1220-1/2		200 (200-1/2)	
LNAV/VNAV DA	1379-3/4		359 (400-3/4)	
LNAV MDA	1460-1/2	440 (500-1/2)	1460-3/4	440 (500-3/4)
CIRCLING	1500-1	469 (500-1)	1500-1 1/2 469 (500-1 1/2)	1620-2 589 (600-2)

ST. CLOUD, MINNESOTA

Amdt 1A 29MAR18

45°33'N-94°04'W

ST CLOUD RGNL (STC)

RNAV (GPS) RWY 31