

WAAS CH 69623 W27A	APP CRS 270°	Rwy Idg TDZE 239 Apt Elev 246	4271
--	------------------------	---	-------------

RNAV (GPS) RWY 27

WINDHAM (IJD)


▼

▲

Procedure NA at night. DME/DME RNP-0.3 NA. Rwy 27 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Windsor Locks altimeter setting and increase all MDA 80 feet, and increase Cat B visibility ¼ mile, and increase Cat C visibility ½ mile.

MISSED APPROACH:
Climbing left turn to
2600 direct ORW
VOR/DME and hold.

ASOS 133.675	YANKEE APP CON 127.8 269.325	CLNC DEL 128.6	UNICOM 122.975 (CTAF) 0
------------------------	--	--------------------------	-----------------------------------



ELEV 246	TDZE 239	Visual Segment - Obstacles.	HHOTT	4 NM Holding Pattern
2600	ORW	HUVUX 3.1 NM to RW27	LINKS	2500
270° to RW27		2200		
3.1 NM	2.9 NM	6 NM		
CATEGORY	A	B	C	D
LP MDA	940-1 701 (700-1)		940-2 701 (700-2)	NA
LNAV MDA	960-1 721 (800-1)		960-2 721 (800-2)	NA
CIRCLING	960-1 714 (800-1)		980-2 734 (800-2)	NA