


WAAS CH 50117 W15A	APP CRS 147°	Rwy Idg TDZE 417 Apt Elev 421
--	------------------------	---


RNAV (GPS) RWY 15
SYRACUSE HANCOCK INTL (SYR)

RNP APCH. ▼ Rwy 15 helicopter visibility reduction below ¾ SM NA. ▲ Inop table does not apply to LPV DA all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C.	MALS A4	MISSED APPROACH: Climb to 1600 then climbing left turn to 3200 direct STODA and hold, continue climb-in-hold to 3200.
--	------------	---

ATIS 124.225	SYRACUSE APP CON 126.125 269.125	SYRACUSE TOWER 120.3 239.0	GND CON 121.7 348.6	CLNC DEL 125.05 257.775
------------------------	--	--------------------------------------	-------------------------------	-----------------------------------



ELEV 421	D	TDZE 417
-----------------	----------	-----------------



ELESE		NADSY		1600	3200	STODA
3000		2300		*1.3 NM to RWY 15		
GP 3.00°		2300		*LNAV only.		
TCH 53		5.9 NM		4.5 NM		1.3 NM
CATEGORY	A	B	C	D		
LPV DA	667-¾		250 (300-¾)			
LNAV/VNAV DA	894-1½		477 (500-1½)			
LNAV MDA	880-¾ 463 (500-¾)		880-1½ 463 (500-1½)			
CIRCLING	900-1 479 (500-1)	920-1 499 (500-1)	1020-1½ 599 (600-1½)	1180-2½ 759 (800-2½)		

TDZ/CL Rwy 28
HIRL Rwy 10-28 and 15-33