

WAAS CH 66034 W10A	APP CRS 120°	Rwy ldg TDZE 589 Apt Elev 592
--	------------------------	---

RNAV (GPS) RWY 10L

NIAGARA FALLS INTL (IAG)

▼

DME/DME RNP-0.3 NA. VDP NA with Buffalo Niagara Intl altimeter setting. When local altimeter setting not received, use Buffalo Niagara Intl altimeter setting and increase all MDA 60 feet.

▲

Increase LP Cats C/D and Circling Cats C/D visibility ¼ mile. Rwy 10L helicopter visibility reduction below ¾ SM NA. Rwy 6, 10R, 24, 28L helicopter visibility reduction below 1 SM NA. Circling Rwy 6, 10R, 24, 28L NA at night.

MISSED APPROACH: Climb to 1100 then climbing left turn to 3600 direct DIONE and hold.

ATIS	BUFFALO APP CON	NIAGARA TOWER ★	GND CON	CLNC DEL	UNICOM
120.8 269.4	126.5 317.6	118.5 (CTAF) 0 349.0	125.3 275.8	119.25 251.1	122.95

ELEV 592 **D** TDZE 589

TDZ/CL Rwy 28R

REIL Rwy 6, 10R, 24, and 28L

HIRL Rwy 10L-28R

MIRL Rwy 6-24 and 10R-28L

NIAGARA FALLS, NEW YORK

Orig-A 22JUN17

43°06'N-78°57'W

RNAV (GPS) RWY 10L