

WAAS

CH **72937**

W34A

APP CRS

339°

Rwy Idg

5402

TDZE

204

Apt Elev

207

RNAV (GPS) RWY 34

HANOVER COUNTY MUNI (OF P)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Richmond Intl altimeter setting and increase all DA 37 feet and all MDA 40 feet; increase LNAV/VNAV all Cats and LNAV Cats C/D visibility ½ mile. Baro-VNAV and VDP NA when using Richmond Intl altimeter setting.

MISSED APPROACH:

Climb to 700 then climb to 2000 direct COATT and hold.

ASOS 119.025	POTOMAC APP CON 126.75 307.2	CLNC DEL 125.4	UNICOM 122.7 (CTAF) 0
------------------------	--	--------------------------	---------------------------------

MISSED APCH FIX

COATT

165°

345°

4 NM

MSA RW34 25 NM

2600

Λ 991

Λ 660

Λ 644

352

309±

339°

537

1002

1053

1587

1900

349°

169°

349°

4 NM

(IF/IAF) RIC RICHMOND

DWEED 2.6 NM to RW34

RW34

NoPT for arrivals on RIC VORTAC
airway radials 105 CW 248.

700

2000

COATT

△

4 NM Holding Pattern

RIC VORTAC

169°→ 2000

← 349°

349°

1900

339°

*1060

DWEED 2.6 NM to RW34

*1 NM to RW34

RW34

1 NM

1.6 NM

2.6 NM

8 NM

GP 3.00°

TCH 50

5402 X 100

34

REIL Rws 16 and 34 339° to RW34

MIRL Rwy 16-34

ELEV 207	TDZE 204				
		*LNAV only.			
		CATEGORY			
		LPV DA			
		LNAV/VNAV DA			
		LNAV MDA			
		CIRCLING			

RICHMOND/ASHLAND, VIRGINIA

Orig 25JUN15

37°42'N-77°26'W

HANOVER COUNTY MUNI (OF P)

RNAV (GPS) RWY 34