

WAAS
CH **78412**
W26A

APP CRS
254°

Rwy Idg
TDZE **1487**
Apt Elev **1497**

RNAV (GPS) RWY 26

EASTERN OREGON RGNL AT PENDLETON (PDT)

RNP APCH.

▼

▲

⊞

Circling Rwy 11 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500.
#RVR 1800 authorized with the use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 4300 direct CESMI and on track 261° to PDT VORTAC and hold, continue climb-in-hold to 4300.

ASOS 118.325	CHINOOK APP CON * 133.15 379.15	PENDLETON TOWER * 119.7 (CTAF) 257.8	GND CON 121.9 257.8	UNICOM 122.95
------------------------	---	--	-------------------------------	-------------------------

Procedure NA for arrivals at ALW VOR/DME on V536 northeast bound.

MSA RW26 25 NM
6700
2435

ELEV **1497**

D

TDZE **1487**

Procedure NA for arrivals at LACED on V4 southeast bound.

4300

CESMI

tr 261°

PDT

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 48).

FAVUB

REYOT

GARYC

* LNAV only

SAYOS
2.5 NM to RW26

* 1.1 NM to RW26

RW26

2320*

4300

254°

5600

GP 3.00°
TCH 55

CATEGORY	A	B	C	D
LPV DA#	1687/24 200 (200-½)			
LNAV/VNAV DA	1800/24 313 (400-½)			
LNAV MDA	1880/24 393 (400-½)	1880/40 393 (400-¾)		
CIRCLING	1920-1 423 (500-1)	1960-1 463 (500-1)	1980-1½ 483 (500-1½)	2200-2¼ 703 (800-2¼)

REIL Rwy 11 and 29
MIRL Rwy 11-29
HIRL Rwy 8-26

PENDLETON, OREGON
Orig-F 31DEC20

EASTERN OREGON RGNL AT PENDLETON (PDT)
45°42'N-118°51'W

RNAV (GPS) RWY 26