

WAAS CH <b>40303</b> <b>W21A</b>	APP CRS <b>211°</b>	Rwy Idg TDZE <b>404</b> Apt Elev <b>410</b>
--	------------------------	---

RNAV (GPS) Y RWY 21R

TRI-CITIES (PSC)

⚠

Baro-VNAV NA when using Hermiston altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP NA with Hermiston altimeter setting. When local altimeter setting not received, use Hermiston altimeter setting and increase all DA 95 feet and all MDA 100 feet; increase LNAV/VNAV all Cats visibility 3⁄8 mile; LNAV Cat C and D visibility 3⁄8 mile and Circling Cat C and D visibility 1⁄4 mile.

# RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using Hermiston altimeter setting.

MALSR

MISSED APPROACH:

Climb to 1100 then climbing right turn to 5200 direct PAIDS and hold, continue climb-in-hold to 5200.

ATIS <b>125.65</b>	CHINOOK APP CON* <b>128.75 377.2</b>	TRI-CITIES TOWER* <b>135.3 (CTAF) 0 323.3</b>	GND CON <b>121.8</b>	CLNC DEL <b>120.0</b>	UNICOM <b>122.95</b>
-----------------------	---	--	-------------------------	--------------------------	-------------------------

MISSED APCH FIX

Procedure NA for arrivals at PSC VOR/DME on V187 southeast bound and on V520 westbound.

ELEV 410

TDZE 404

1100		5200	PAIDS
*LNAV only			
CATEGORY	A	B	C
LPV DA#		604/24	200 (200-1⁄2)
LNAV/VNAV DA		844/51	440 (500-1)
LNAV MDA	940/24	536 (600-1⁄2)	940/55 536 (600-1)
CIRCLING	940-1	530 (600-1)	1040-1 3⁄4 630 (700-1 3⁄4) 1100-2 1⁄4 690 (700-2 1⁄4)

REIL Rwy 3L and 12

MIRL Rwy 12-30

HIRL Rwy 3L-21R

PASCO, WASHINGTON  
Amdt 2B 07DEC17

46°16'N-119°07'W

TRI-CITIES (PSC)

RNAV (GPS) Y RWY 21R