

LOC I-PLH 111.7	APCH CRS 308°	Rwy Idg 10,000 TDZE 1276 Arprt Elev 1291	AL-299 [USAF]	TINKER AFB	(KTIK)
---------------------------	-------------------------	---	---------------	------------	--------

* When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile,
CAT CDE vis to 1½.
** CAT E Circling not authorized in sector S of Rwy
13-31 and W of Rwy 18-36.

ATIS ★ 270.1	OKE CITY APP CON 120.45 288.325	TINKER TOWER 124.45 251.05	GND CON 121.8 275.8	CLNC DEL 119.7 335.8	ASR
------------------------	---	--------------------------------------	-------------------------------	--------------------------------	-----

When VGSI inop, procedure NA at night

† MISSED APPROACH: Climb straight ahead to 2500, then turn right to 4000 direct I-PLH and TIK 13 DME (BURVE) and hold.

† Missed approach requires use of RNAV or ATC radar monitoring.

RADAR REQUIRED
EMERG SAFE ALT 100 NM 4700

ELEV 1291	TDZE 1276
-----------	-----------

CATEGORY	A	B	C	D	E
S-LOC 31*	1740/50 464 (500-1)		1740/60 464 (500-1½)		
CIRCLING **	1840-1 549 (600-1)		1960-1¾ 669 (700-1¾)	1980-2¼ 689 (700-2¼)	1960-2¼ 669 (700-2¼)

FAF to MAP 4.5 NM

Knots	60	90	120	150	180
Min:Sec	4:30	3:00	2:15	1:48	1:30