

LOC/DME I-MFE 111.7 Chan 54	APP CRS 137°	Rwy Idg 6983 TDZE 107 Apt Elev 107
---	------------------------	---


ILS or LOC RWY 14
MC ALLEN MILLER INTL (MF'E)

⚠ Circling NA northeast of Rwy 14-32. ADF required. When local altimeter setting not received, use Weslaco altimeter setting: increase all DA 39 feet; increase all MDA 40 feet and S-LOC 14 Cat C/D and Circling Cat C visibility 1/8 mile, increase LOBIC Fix Minimums S-LOC 14 Cat C/D visibility 1/4 mile.


MALSR

MISSED APPROACH: Climb to 1500 then climbing left turn to 2000 direct to MISSI LOM and hold.

ATIS 128.5	VALLEY APP CON 121.0 377.2	MC ALLEN TOWER ★ 118.5 (CTAF) 0 256.9	GND CON 121.8	UNICOM 122.95
----------------------	--------------------------------------	---	-------------------------	-------------------------



ELEV 107	D	TDZE 107
----------	----------	----------



REMAIN WITHIN 10 NM		MISSI LOM/I-MFE 6.8	1500	2000	MF
*660 when using Weslaco altimeter setting.		LOBIC I-MFE 2.7	*LOC only.		
CATEGORY		A	B	C	D
S-ILS 14		307-1/2 200 (200-1/2)			
S-LOC 14		620-1/2	513 (600-1/2)	620-1	513 (600-1)
C CIRCLING		620-1	513 (600-1)	620-1 1/2 513 (600-1 1/2)	800-2 1/4 693 (700-2 1/4)
LOBIC FIX MINIMUMS					
S-LOC 14		540-1/2	433 (500-1/2)	540-3/4	433 (500-3/4)
C CIRCLING		580-1	473 (500-1)	580-1 1/2 473 (500-1 1/2)	800-2 1/4 693 (700-2 1/4)

SC-3, 31 DEC 2020 to 28 JAN 2021

SC-3, 31 DEC 2020 to 28 JAN 2021