

WAAS
CH **50139**
W34A

APP CRS
337°

Rwy Idg
TDZE **769**
Apt Elev **774**

5001
769
774

RNAV (GPS) RWY 34
CASTROVILLE MUNI (CVB)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Lackland AFB (Kelly Fld Annex) altimeter setting: increase all DA/MDA 60 feet and all visibilities ¼ mile. Helicopter visibility reduction below ¾ SM NA. Night landing: Rwy 16 NA.

MISSED APPROACH: Climb to 1300 then climbing left turn to 3000 direct SHEOL and hold.

AWOS-3 119.25	HDO ASOS 119.675	SAN ANTONIO APP CON 118.05 353.5	UNICOM 122.8 (CTAF) 0
-------------------------	----------------------------	--	---------------------------------

The main chart illustrates the RNAV (GPS) RWY 34 approach. Key features include:

- Waypoints:** KICED, 1306, 1261, 824±, TAAHD (1.6 NM to RW34), (FAF) IBDOW, 2500, (IF/IAF) SHEOL, and (IAF) SOMER.
- Altitudes:** 1368, 970±, 1087, 1021, 2500, 3000 NoPT (7.3), and 1300.
- Angles:** 134°, 320 to SHEOL, 337°, 157°, 263° (7.3), and 337°.
- Distances:** 4 NM, 1.6 NM, 3.7 NM, and 6 NM.
- Obstacles:** 1306, 1261, 824±, 1087, 1021, and 1368.
- Procedure:** Procedure NA for arrivals at SOMER on V17 northbound.
- MSA:** MSA RW34 25NM with a 4100' obstacle.

ELEV **774**

TDZE **769**

MIRL Rwy 16-34

1300	3000	SHEOL	IBDOW	TAAHD 1.6 NM to RW34	RW34	*1300	2500	337°	157°	3000	4 NM Holding Pattern	GP 3.00° TCH 40
*LNAV only.												
1.6 NM		3.7 NM		6 NM								
CATEGORY	A		B		C		D					
LPV DA	1019-7/8		250 (300-7/8)				NA					
LNAV/VNAV DA	1127-1¼		358 (400-1¼)				NA					
LNAV MDA	1200-1		431 (500-1)		1200-1½ 431 (500-1½)		NA					
CIRCLING	1200-1 426 (500-1)		1380-1 606 (700-1)		1580-2¼ 806 (900-2¼)		NA					

CASTROVILLE, TEXAS

Amtd 1 15OCT15

29°21'N-98°51'W

CASTROVILLE MUNI (CVB)

RNAV (GPS) RWY 34