

WAAS
CH **63203**
W18A

APP CRS
182°

Rwy Idg
TDZE **264**
Apt Elev **264**

8003

RNAV (GPS) RWY 18

GOLDEN TRIANGLE RGNL (GTR)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALSR, increase LPV Cat E visibility ½ mile, increase LNAV/VNAV Cat E and LNAV Cat E visibility ½ mile. When local altimeter setting not received, use Columbus AFB altimeter setting and increase all DA 39 feet and all MDA 40 feet; increase LNAV/VNAV all Cats and LNAV Cats C/D/E visibility ⅓ mile. For inop MALSR when using Columbus AFB altimeter setting, increase LPV Cat E visibility ¼ mile, increase LNAV/VNAV Cat E and LNAV Cat E visibility ½ mile. Baro-VNAV and VDP NA when using Columbus AFB altimeter setting.

MALSR

MISSED APPROACH:

Climb to 800 then climbing right turn to 3000 direct HUYKA and hold.

ATIS
126.375

COLUMBUS APP CON★
135.6 323.275

GOLDEN TRIANGLE TOWER★
118.2 (CTAF) 0 298.875

GND CON
135.375 322.475

CLNC DEL
135.375 322.475

973

30 NM to HUYKA (NoPT)
4000

1.3 NM to HUYKA
3000
HUYKA

092° 272°

HUYKA
3000

092° 272°

30 NM to HUYKA

7 NM

002°

182°

2000 (6.3)

(IF/IAF) HUYKA

Columbus AFB

A-440

McCharen Field

(FAF) KEKWO

RW18

Λ 593

Λ 449

ELEV 264

TDZE 264

8003 X 150

36

182° to RW18

81

A5

TWR 346

800

3000

HUYKA

* LNAV only.

* 1.1 NM to RW18

RW18

2000

KEKWO

HUYKA

7 NM Holding Pattern

002°

182°

3000

GP 3.00°

TCH 58

1.1 NM

4.2 NM

6.3 NM

CATEGORY	A	B	C	D	E
LPV DA	464-½		200 (200-½)		
LNAV/VNAV DA	670-⅞		406 (500-⅞)		
LNAV MDA	660-½ 396 (400-½)		660-⅝ 396 (400-⅝)		
CIRCLING	760-1	496 (500-1)	960-2 696 (700-2)	960-2¼ 696 (700-2¼)	960-2½ 696 (700-2½)

HIRL Rwy 18-36

CIRCLING

COLUMBUS/WESTPOINT/STARKVILLE, MISSISSIPPI

Amtd 2 08JAN15

33°27'N-88°35'W

GOLDEN TRIANGLE RGNL (GTR)

RNAV (GPS) RWY 18