

WAAS CH <b>42718</b> <b>W36A</b>	APP CRS <b>360°</b>	Rwy Idg TDZE Apt Elev	<b>5001</b> <b>43</b> <b>47</b>
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 36

HAMMOND NORTHSORE RGNL (HDC)

▼

Baro-VNAV NA when using Louis Armstrong New Orleans Intl altimeter setting.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting and increase all DA 89 feet and all MDA 100 feet, increase LPV all Cats visibility ½ mile, LNAV/VNAV all Cats ¼ mile, LNAV Cat C and Circling Cat D ¼ mile, and LNAV Cat D ½ mile. VDP NA with Louis Armstrong New Orleans Intl altimeter setting.

MISSED APPROACH: Climb to 1800 direct BARUN and hold.

ATIS <b>118.325</b>	NEW ORLEANS APP CON <b>119.3 350.35</b>	HAMMOND TOWER ★ <b>120.575</b> (CTAF) <b>0</b>	GND CON <b>119.85</b>	CLNC DEL <b>119.3</b> (When twr closed)
------------------------	--	---	--------------------------	---

Procedure Turn NA	GP 3.00° TCH 52	1800	1800	1800	1800	BARUN
		2200	1800	1800	1800	
		360°	360°	360°	360°	
		6 NM	3.5 NM	0.6 NM	1.2 NM	
CATEGORY	A	B	C	D		
LPV DA		293-¾	250 (300-¾)			
LNAV/VNAV DA		447-1½	404 (400-1½)			
LNAV MDA	460-1	417 (500-1)	460-1¼	417 (500-1¼)		
CIRCLING	500-1	453 (500-1)	500-1½	620-2		
			453 (500-1½)	573 (600-2)		

HAMMOND, LOUISIANA  
Orig 29JUL10

30°31'N-90°25'W

HAMMOND NORTHSORE RGNL (HDC)  
RNAV (GPS) RWY 36

SC-4, 31 DEC 2020 to 28 JAN 2021

SC-4, 31 DEC 2020 to 28 JAN 2021