

LOC/DME I-CH  
**111.5**  
Chan **52**

APP CRS  
**359°**

Rwy ldg **5000**  
TDZE **343**  
Apt Elev **355**

ILS or LOC RWY 36

NACOGDOCHES A L MANGHAM JR RGNL (OCH)

ADF required. When local altimeter setting not received, use Lufkin altimeter setting and increase all DA 56 feet and all MDA 60 feet and increase all S-LOC 36 Cat C visibilities ¼ SM. VDP NA when using Lufkin altimeter setting. Localizer unusable inside 0.3 NM from threshold.  
Autopilot coupled approach NA below 740.

MALSR

MISSED APPROACH: Climb to 1000 then climbing left turn to 2100 direct NADOS/OC NDB and hold.

AWOS-3PT <b>135.625</b>	HOUSTON CENTER <b>125.175 285.575</b>	UNICOM <b>123.0 (CTAF) 1</b>
----------------------------	--	---------------------------------

\*820 when using Lufkin altimeter setting.

One Minute Holding Pattern

OC NDB I-CH (6.1)

CATEB I-CH (2.6)

ZITGI I-CH (1.3)

\*I-CH (1.9)

\*LOC only.

2100

179°

359°

359°

760

3.5 NM

0.7 NM

0.7 NM

0.3

GS 3.00°

TCH 53

CATEGORY	A	B	C	D
S-ILS 36	543-½	200 (200-½)		NA
S-LOC 36	760-½	417 (500-½)	760-¾ 417 (500-¾)	NA
CIRCLING	860-1	505 (600-1)	860-1½ 505 (600-1½)	NA
CATEB FIX MINIMUMS (DME REQUIRED)				
S-LOC 36	700-½	357 (400-½)	700-¾ 357 (400-¾)	NA
CIRCLING	860-1	505 (600-1)	860-1½ 505 (600-1½)	NA

ELEV 355

TDZE 343

MIRL Rwy 18-36 1

REIL Rwy 18 1

81

5000 x 75

36

359° 5.1 NM from FAF

FAF to MAP 4.8 NM

Knots	60	90	120	150	180
Min:Sec	4:48	3:12	2:24	1:55	1:36

NACOGDOCHES, TEXAS

Amcl 3E 22JUN17

NACOGDOCHES A L MANGHAM JR RGNL (OCH)

31°35'N-94°43'W

ILS or LOC RWY 36