

APP CRS	Rwy Idg	5000
183°	TDZE	372
	Apt Elev	372

RNAV (GPS) RWY 19

STURGIS MUNI (TWT)

NA

DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Henderson altimeter setting and increase all MDA 60 feet, increase LNAV Cats C and D visibility ½ mile and Circling Cat C ¼ mile.

MISSED APPROACH:

Climb to 2500 direct FITIP and hold.

AWOS-3 118.775	EVANSVILLE APP CON ★ 124.025 290.9	UNICOM 122.8 (CTAF) 0
-------------------	---------------------------------------	--------------------------

The main chart displays the RNAV (GPS) RWY 19 approach. Key features include:

- Initial Descent:** 183° to RW19, 6.1 NM, 5000 x 75 ft.
- Waypoints:** (IAF) IKELE, (IF/IAF) OLGEV, (FAF) COVOS, RW19.
- Altitudes:** 1093, 668, 392, 1700, 183, 2500, 2600, 123, 123° (5), 183° (6.6), 1700, 688±, 392.
- Angles:** 123°, 183°, 243°, 003°.
- Distances:** 4 NM, 30 NM to OLGEV, 30 NM to IKELE, 1.5 NM to IKELE, 30 NM to HETEP.
- Obstacles:** 1093, 668, 1007.
- Navigation Aids:** 183° to RW19, 183° to HETEP, 003° to HETEP.

ELEV 372

TDZE 372

183° to RW19

6.1

5000 x 75

1

REIL Rwy 1 and 19 0

MIRL Rwy 1-19 0

MISSED APCH FIX

FITIP

003°

183°

4 NM

2500

FITIP

OLGEV

4 NM Holding Pattern

003°

183°

2500

COVOS

1700

3.50°

TCH 30

3.5 NM

6.6 NM

RW19

CATEGORY	A	B	C	D
LNAV MDA	940-1	568 (600-1)	940-1½	568 (600-1½)
CIRCLING	940-1 568 (600-1)	1000-1 628 (700-1)	1000-1¾ 628 (700-1¾)	1120-2½ 748 (800-2½)

STURGIS, KENTUCKY  
Amdt 1A 18SEP14

37°33'N-87°57'W

STURGIS MUNI (TWT)

RNAV (GPS) RWY 19

SE-1, 31 DEC 2020 to 28 JAN 2021

SE-1, 31 DEC 2020 to 28 JAN 2021