

WAAS  
CH **70300**  
**W05A**

APP CRS  
**055°**

Rwy Idg  
TDZE **716**  
Apt Elev **748**

**RNAV (GPS) Y RWY 5**  
CHARLOTTE/DOUGLAS INTL (CLT)

▼

Circling NA at night. For inop MALSR, increase LNAV/VNAV all Cats visibility to 1½ SM and LNAV Cat C/D visibility to 1¼ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. \*\* RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 4000 direct ATELL and hold, continue climb-in-hold to 4000.

D-ATIS	CHARLOTTE APP CON	CHARLOTTE TOWER	GND CON	CLNC DEL
ARR <b>121.15</b> DEP <b>132.1</b>	(001°-119°) <b>128.32</b> (120°-295°) <b>120.05</b> (296°-360°) <b>134.75</b> (180°-359°) <b>257.2</b> (360°-179°) <b>307.8</b>	(Rwys 18L-36R, 5-23) <b>118.1 257.8</b> (Rwy 18C-36C) <b>126.4 257.8</b> (Rwy 18R-36L) <b>133.35 257.8</b>	<b>121.8 348.6 (WEST)</b> <b>121.9 348.6 (EAST)</b>	<b>127.15</b> <b>348.6</b>

2754

**RADAR REQUIRED**

KECKS

4000

055°

2500

ERKAW

2500

1.7 NM to RW05

RW05

6 NM

3.7 NM

1.7 NM

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 89).

4000

ATELL

\*LNAV only.

CATEGORY	A	B	C	D
LPV DA **	916/24		200 (200-½)	
LNAV/VNAV DA	1229/55		513 (600-1)	
LNAV MDA	1320/24 604 (700-½)		1320/55 604 (700-1)	
CIRCLING	1380-1 632 (700-1)		1500-2¼ 752 (800-2¼) 1500-2½ 752 (800-2½)	

ELEV 748

 TDZE 716

CHARLOTTE, NORTH CAROLINA  
Amdt 3C 24MAY18

35°13'N-80°57'W

CHARLOTTE/DOUGLAS INTL (CLT)  
**RNAV (GPS) Y RWY 5**