

WAAS CH 70710 W09A	APP CRS 088°	Rwy Idg 6502 TDZE 147 Apt Elev 147
--	------------------------	---

RNAV (GPS) RWY 9
FLORENCE RGNL (FLO)

T Night landing: Rw (1, 19 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Darlington altimeter setting and increase LPV DA to 489 feet, LNAV/VNAV DA to 695 feet and all visibilities to 1¼ miles; increase all MDA 60 feet and LNAV Cat C visibility ¼ mile. For inoperative MALSR when using Darlington altimeter setting, increase LPV all Cats visibility to 1¼ mile. Baro-VNAV and VDP NA when using Darlington altimeter setting.

MALSR



MISSED APPROACH:
Climb to 2000 direct
ESVAC and hold.

ATIS 123.625	FLORENCE APP CON★ 118.6 341.7 (256°-074°) 135.25 316.15 (075°-255°)	FLORENCE TOWER★ 125.1 (CTAF) 0 353.85	GND CON 121.9 353.85	CLNC DEL 121.9 353.85	UNICOM 122.95
-----------------	---	--	-------------------------	--------------------------	------------------

