

AWOS-3  
128.175  
CLNC DEL  
121.75 254.375  
GND CON  
121.75 254.375  
STANLY COUNTY TOWER ★  
126.275 (CTAF) 291.9  
UNICOM  
123.0  
CHARLOTTE DEP CON  
128.325 307.8

TOP ALTITUDE:  
3000

TAKEOFF MINIMUMS  
Rwys 4L, 22R: NA.  
Rwy 22L: Standard.  
Rwy 4R: 300-1½ or standard with minimum  
climb of 276' per NM to 1000.

- NOTE: For turbojets only.  
NOTE: DME/DME/IRU or GPS required.  
NOTE: RNAV 1.  
NOTE: RADAR required.  
NOTE: If unable to accept climb rates,  
advise ATC on initial contact.  
NOTE: Upon reaching 10000 MSL, accelerate to  
and maintain 280K, if unable advise ATC.  
NOTE: Transponder code will be issued via PDC  
or Charlotte CLNC DEL.

NOTE: Chart not to scale.

▼

DEPARTURE ROUTE DESCRIPTION

Climb on heading assigned by ATC, expect RADAR vectors to HMMPY,  
then on track 181° to KWEEN, then on assigned transition, maintain  
3000, expect filed altitude within 10 minutes after departure.

PITRW TRANSITION (KWEEN4.PITRW)  
UNJAM TRANSITION (KWEEN4.UNJAM)

