

APP CRS
095°

Rwy Idg
TDZE
Apt Elev

9000
1000
1026

RNAV (RNP) Z RWY 10

HARTSFIELD-JACKSON ATLANTA INTL (ATL)

▽

For uncompensated Baro-VNAV systems, procedure NA below -8°C (18°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized; arrival from ROBNS NA. For inop ALS, increase RNP 0.11 DA all Cats visibility to RVR 4500.

ALSF-2

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct SCARR and hold.

D-ATIS ARR 119.65	ATLANTA APP CON	ATLANTA TOWER						ALL RWYS	GND CON	ALL RWYS
DEP 125.55	127.9 379.9	8L-26R	8R-26L	9L-27R	9R-27L	10-28			(8L-26R,8R-26L) (9L-27R,9R-27L)	10-28
		119.1	125.325	123.85	119.3	119.5	254.4		121.9	121.75 121.65 254.4

2049

2049

2049

2049

CNLC
DEL
118.1

CPDLC

4000 095° (2.9)

(IAF) GAAIN

(IF) CTEEE 2700 095° (5)

(FAF) ZMANN 1179

(5.2)

1311

1174

1260

6000 275° (6.3)

(IAF) ROBNS 8000 (RF REQD)

ELRAY 210K

MSA RW 10 25 NM

3100

MISSED APCH FIX

SCARR

185°

005°

4 NM

ELEV 1026

D TDZE 1000

CTEEE

4000

095°

2700

ZMANN

2700

RW10

GP 3.00° TCH 55

5 NM

5.2 NM

CATEGORY	A	B	C	D
RNP 0.11 DA		1290/24	290 (300-½)	
RNP 0.30 DA		1456/50	456 (500-1)	

AUTHORIZATION REQUIRED

HIRL all Rwys

TDZ/CL Rwys 8L, 9R, 10, 26R, 27L and 28

ATLANTA, GEORGIA

Amdt 1 12OCT17

HARTSFIELD-JACKSON ATLANTA INTL (ATL)

33°38'N-84°26'W

RNAV (RNP) Z RWY 10